

Safety Data Sheet

25% Carbon Dioxide, 75% Argon

Section 1: Product and Company Identification

American Welding & Gas, Inc. 4900 Falls of Neuse Road, Suite 150 Raleigh, NC 27609 1-800-967-6874 http://www.awggases.com

Product Code: 25% Carbon Dioxide, 75% Argon

Synonyms: Recommended Use: Usage Restrictions:

Section 2: Hazards Identification



Hazard Classification: Gases Under Pressure

Hazard Statements:

Contains gas under pressure; may explode if heated

Precautionary Statements

Storage:

Protect from sunlight. Store in well-ventilated place.

Section 3: Composition/Information on Ingredients

	CAS#	Concentration		
Carbon Dioxide	124-38-9	25%		
Argon	7440-37-1	75%		

American Welding & Gas, Inc. Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved page 1 of 6

Date of Preparation: 04/25/2019 12:12:17

	Chemical Substance	Chemical Family	Trade Names
Carbon Dioxide	CARBON DIOXIDE, GAS	Inorganic gases	CARBONIC ACID GAS; CARBONIC ANHYDRIDE; CARBON DIOXIDE; CARBON OXIDE; UN 1013; CO2
Argon	ARGON, COMPRESSED	Inorganic gases	ARGON; UN 1006; AR

Section 4: First Aid Measures

	Skin Contact	Eye Contact	Ingestion	Inhalation	Note to Physicians
Carbon Dioxide	If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.	Contact with liquid: Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.	Do not induce vomiting.	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.
Argon	Not applicable route of exposure	Flush eyes with plenty of water.	Not applicable route of exposure	If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.	For inhalation, consider oxygen.

Section 5: Fire Fighting Measures

	Suitable Extinguishing Media	Products of Combustion	Protection of Firefighters			
Carbon Dioxide	Non-flammable	Non-flammable	 Any appropriate escape-type, self-contained breathing apparatus. Non-flammable 			
Argon	Non-flammable gas	Not applicable	■ N/A ■ N/A			

Section 6: Accidental Release Measures

	Personal Precautions	Environmental Precautions	Methods for Containment
Carbon Dioxide	Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering. Do not touch spilled material.	Subject to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). Keep out of water supplies and sewers.	Stop leak if possible without personal risk.
Argon	Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.	None known.	Stop leak if possible without personal risk.

	Methods for Cleanup	Other Information
Carbon Dioxide	Stop leak, evacuate, remove source of ignition.	None
Argon	Leaks may be detected by a soapy-water solution.	

American Welding & Gas, Inc. Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved

Section 7: Handling and Storage

	Handling	Storage
Carbon Dioxide	Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.	Store and handle in accordance with all current regulations and standards
Argon	Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.	Avoid using in confined spaces.

Section 8: Exposure Controls/Personal Protection

	Exposure Guidelines
Carbon	CARBON DIOXIDE, GAS: CARBON DIOXIDE: 5000 ppm (9000 mg/m3) OSHA TWA 10000 ppm (18000 mg/m3) OSHA TWA
Dioxide	(vacated by 58 FR 35338, June 30, 1993) 30000 ppm (54000 mg/m3) OSHA STEL (vacated by 58 FR 35338, June 30, 1993)
	5000 ppm ACGIH TWA 30000 ppm ACGIH STEL 5000 ppm (9000 mg/m3) NIOSH recommended TWA 10 hour(s) 30000 ppm
	(54000 mg/m3) NIOSH recommended STEL
Argon	ARGON, COMPRESSED: ARGON: ACGIH (simple asphyxiant)

Engineering Controls

Handle only in fully enclosed systems.

	Eye Protection	Skin Protection	Respiratory Protection
Carbon	For the gas: Eye protection not required, but recommended. For	For the gas: Protective clothing is	Any appropriate
Dioxide	the liquid: Wear splash resistant safety goggles. Contact lenses	not required. For the liquid: Wear	escape-type, self-
	should not be worn. Provide an emergency eye wash fountain and	appropriate protective, cold	contained breathing
	quick drench shower in the immediate work area.	insulating clothing.	apparatus.
Argon	Eye protection not required, but recommended.	Protective clothing is not required.	N/A

General Hygiene considerations

- Avoid breathing vapor or mist
- Avoid contact with eyes and skin
- Wash thoroughly after handling and before eating or drinking

Section 9: Physical and Chemical Properties

	Physical State	Appearance	Color	Change in Appearance	Physical Form	Odor	Taste
Carbon Dioxide	Gas	Colorless	Colorless	N/A	Gas	Odorless	Acid taste
Argon	Gas	Colorless	Colorless	N/A	Gas	Odorless	Tasteless

	Flash Point	Flammability	Partition Coefficient	Autoignition Temperature	Upper Explosive Limits	Lower Explosive Limits
Carbon Dioxide	Not flammable	Not available	N/A	Nonflammable	Nonflammable	Nonflammable
Argon	Not flammable			Nonflammable	Nonflammable	Nonflammable

	Boiling Point	Freezing Point	Vapor Pressure	Vapor Density	Specific Gravity	Water Solubility	рН	Odor Threshold	Evaporation Rate	Viscosity
Carbon Dioxide	Not available	-71 F (- 57 C) @ 4000 mmHg	43700 mmHg @ 21 C	1.5 (Air=1)	1.522 @ 21 C	Soluble	3.7 (saturated aqueous solution) @ 101.3 kPa (carbonic acid)	Not available	Not applicable	0.01657 cP @ 0 C
Argon	-303 F (- 186 C)	-308 F (- 189 C)	500 mmHg @ -190 C	1.38 (Air=1)	Not applicable	3.36% @ 20 C	Not applicable	Not available	Not applicable	0.0225 cP @ 25 C

American Welding & Gas, Inc. Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved page 3 of 6

Date of Preparation: 04/25/2019 12:12:17

	Molecular Weight	Molecular Formula	Density	Weight per Gallon	Volatility by Volume	Volatility	Solvent Solubility
Carbon Dioxide	44.01	C-O2	0.114	Not available	Not applicable	Not applicable	Soluble: Alcohol, acetone, hydrocarbons, organic solvents
Argon	39.948	AR	1.784 g/L @ 0 C	Not available	100%	Not applicable	Soluble: Organic solvents

Section 10: Stability and Reactivity

	Stability	Conditions to Avoid	Incompatible Materials
Carbon	Stable at normal temperatures	Stable at normal temperatures	Combustible materials, oxidizing materials, metal salts,
Dioxide	and pressure.	and pressure.	reducing agents, metal carbide, metals, bases
Argon	Stable at normal temperatures	Stable at normal temperatures	No data available.
	and pressure.	and pressure.	

	Hazardous Decomposition Products	Possibility of Hazardous Reactions
Carbon Dioxide	Carbon monoxide	Will not polymerize.
Argon	No data available.	Will not polymerize.

Section 11: Toxicology Information

Acute Effects

	Oral LD50	Dermal LD50	Inhalation
Carbon Dioxide	Not established	Not established	Ringing in the ears, nausea, irregular heartbeat, headache, drowsiness, dizziness, tingling sensation, visual disturbances, suffocation, convulsions, coma
Argon	Not established	Not established	Nausea, vomiting, difficulty breathing, irregular heartbeat, headache, dizziness, disorientation, mood swings, tingling sensation, loss of coordination, suffocation, convulsions, unconsciousness, coma

	Eye Irritation	Skin Irritation	Sensitization
Carbon Dioxide	Irritation, frostbite, blurred vision	Liquid: blisters, frostbite	Difficulty breathing
Argon	No information on significant adverse effects	No information on significant adverse effects	

Chronic Effects

	Carcinogenicity	Mutagenicity	Reproductive Effects	Developmental Effects
Carbon Dioxide	Not available	Not established	Available.	No data
Argon	Not established	Not established	Not established	No data

Section 12: Ecological Information

Fate and Transport

	Eco toxicity	Persistence / Degradability	Bioaccumulation / Accumulation	Mobility in Environment
Carbon Dioxide	Fish toxicity: 150000 ug/L 48 day(s) (Mortality) Brown trout (Salmo trutta) Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Relatively non-persistent in the environment. Moderately volatile from water.	Accumulates very little in the bodies of living organisms.	Leaches through the soil
Argon	Fish toxicity: Not available Invertibrate toxicity: Not available Algal toxicity: Not available Phyto toxicity: Not available Other toxicity: Not available	Not available	Not available	Not available

American Welding & Gas, Inc. Generated by the SDS Manager from AsteRisk, LLC. All Rights Reserved

Section 13: Disposal Considerations

Carbon Dioxide	Dispose in accordance with all applicable regulations.
Argon	Dispose in accordance with all applicable regulations.

Section 14: Transportation Information

U.S. DOT 49 CFR 172.101

DOT Information For This Mixture

Shipping Name	Compressed gas, n.o.s. (Argon, Carbon Dioxide)		
UN Number	UN1956		
Hazard Class	2.2		
Hazard Information	Non-Flammable Gas		

Individual Component Information

	Proper Shipping Name	ID Number	Hazard Class or Division	Packing Group	Labeling Requirements	Passenger Aircraft or Railcar Quantity Limitations	Cargo Aircraft Only Quantity Limitations	Additional Shipping Description
Carbon	Carbon	UN1013	2.2	Not	2.2	75 kg or L	150kg	None
Dioxide	dioxide			applicable				
Argon	Argon,	UN1006	2.2	Not	2.2	75 kg or L	150 kg	N/A
	compressed			applicable				

Canadian Transportation of Dangerous Goods

	Shipping Name	UN Number	Class	Packing Group / Risk Group
Carbon Dioxide	Carbon dioxide	UN1013	2.2	Not applicable
Argon	Argon, compressed	UN1006	2.2	Not applicable

Section 15: Regulatory Information

U.S. Regulations

	CERCLA Sections	SARA 355.30	SARA 355.40	
Carbon Dioxide	Not regulated.	Not regulated.	Not regulated.	
Argon	Not regulated.	Not regulated.	Not regulated.	

SARA 370.21

	Acute	Chronic	Fire	Reactive	Sudden Release
Carbon Dioxide	Yes	No	No	No	Yes
Argon	Yes	No	No	No	Yes

SARA 372.65

Carbon Dioxide	Not regulated.
Argon	Not regulated.

OSHA Process Safety

Carbon Dioxide	Not regulated.
Argon	Not regulated.

State Regulations

	CA Proposition 65
Carbon Dioxide	Not regulated.
Argon	Not regulated.

Date of Preparation: 04/25/2019 12:12:17

Canadian Regulations

	WHMIS Classification
Carbon Dioxide	Α
Argon	Α

National Inventory Status

	US Inventory (TSCA)	TSCA 12b Export Notification	Canada Inventory (DSL/NDSL)
Carbon Dioxide	Listed on inventory.	Not listed.	Listed on inventory.
Argon	Listed on inventory.	Not listed.	Listed on inventory.

Section 16: Other Information

	NFPA Rating
Carbon Dioxide	HEALTH=2 FIRE=0 REACTIVITY=0
Argon	HEALTH=0 FIRE=0 REACTIVITY=0

^{0 =} minimal hazard, 1 = slight hazard, 2 = moderate hazard, 3 = severe hazard, 4 = extreme hazard

page 6 of 6 Date of Preparation: 04/25/2019 12:12:17